

ABB RoomTouch® 4"

As individual as your home



# Transform your smart living experience

With the user-friendly and customizable interface, all functions can be easily controlled, for example, by opening the blinds with a swipe up or closing them with a swipe down. You can also create personalized room scenes, control the panel by swiping through the menu or tapping to confirm an action such as turning on the lights.

- 12 control functions
- KNX Data Secure for maximum data protection
- Up to 12 status information can be shown (e.g. fault / alarm messages)
- One random touch to activate a pre-defined "coming in" scene or function
- · Haptic feedback (vibration)
- · Integrated proximity and brightness sensor
- · Integrated room temperature controller
- Anti-glare mode for use in dark, complementing the day and night mode of the device
- Flexible visualization (1-4 functions per page)
- Integrated binary input and external temperature sensor input





### Simple and flexible use

ABB RoomTouch® 4" can be used for both ABB free@home® as well as for KNX. It picks up the UI of the ABB-free@home® Next app and expands its possibilities:

- · Sleek product design
- Simple UI and easy operability, e.g. of RGB lights or blind positions
- · Clear labeling of the functions
- · Wide viewing angle thanks to its IPS glass display

#### Installation:

ABB RoomTouch® 4" only requires a standard flush mounting box and can therefore be installed quickly and without special accessories.

A 24 V DC supply is required as an additional power supply, which can be implemented, for example, via the second pair of wires in the bus line.



Compatibility with ABB i-bus® KNX, ABB-free@home®; optional coupling with external temperature sensors or conventional switches



**Slim & timeless design** in black and white with IPS glass display



Global availability thanks to compliance to standards including VDE, British Standard, and Swiss standard with standard installation boxes



Smooth usability when swiping with clear readability, flexible visualization (1-4 functions per page) and user-friendly UI





## **Ordering data**

Description	Order code
ABB RoomTouch® 4", 1-12-fold, white	RT/U12.86.1-811
ABB RoomTouch® 4", 1-12-fold, black	RT/U12.86.1-825
Anti-theft protection for control elements	TZE/U.0.1CK
Anti-theft protection	TZW/U.0.1CK

For additional protection, e.g. in public areas, the display can be optionally equipped with anti-theft protection to prevent removal or sabotage of the display.

#### Commissioning via ETS5/6 and DCA tool:

In ABB-free@home®, the display is commissioned via the configuration interface of the System Access Point. Commissioning in the ETS (KNX) takes place via the DCA (Device Commissioning Application).



# One design family

#### ABB RoomTouch® 4"







### ABB RoomTouch® 5"







### ABB SmartTouch® 10"

Door Entry (2 wire)











### **Contact**

\_

**Busch-Jaeger Elektro GmbH** 

Freisenbergstraße 2 58513 Lüdenscheid, Deutschland info.bje@de.abb.com

Contact us:

Tel.: +49 (0) 2351 956-1600 Fax: +49 (0) 2351 956-1700

www.abb.com/knx

We reserve the right to make technical modifications to products as well as changes to the contents of this document without prior notice. The respective agreed-upon conditions apply to orders. ABB accepts no responsibility for possible errors or incompleteness in this document.

We reserve all rights to this document and the topics and illustrations contained therein. Duplication, disclosure to third parties or the use of its contents – and of parts thereof – is forbidden without prior written approval from ABB.