

AUDIO AMPLIFIER/RECEIVER/MIXER



Specifications

| | |
|----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| Amplifier Output Power | 50 W RMS, 2 x 25 W channels |
| Receiver Input | Infrared FM, 2 wireless mic channels |
| Modulation | Wide-band FM |
| Reception Frequencies | Ch. A: 2.08 MHz Ch. B: 2.54 MHz |
| Deviation | 10 kHz Nominal, 25 kHz Maximum |
| De-emphasis | 50 μ s |
| Tone Key | 32.768 kHz |
| Infrared Wavelength | 850 nm |
| External Sensor Input | 2, RCA, powered ports |
| Connectivity Coverage | 1,600 sq ft per sensor, up to 3 sensors supported |
| Total Harmonic Distortion | <1% @ 1 kHz |
| Frequency Response | 40 Hz – 18 kHz, \pm 3 dB |
| Line Level Inputs | Rear Panel: DVD input, dual RCA, 0dB Rear Panel: Computer input, 3.5mm, -10 dB Front panel: Auxiliary input, 3.5 mm, -10 dB |
| Anti-Hum Balun | Present on Computer input |
| Line Outputs | Front panel: 3.5mm w/ gain control Rear Panel: 3.5 mm w/ +10 dB gain control |
| Output Impedance | Rated Load: 4 Ω minimum impedance |
| Equalization | 3-band, \pm 10 dB |
| S/N Ratio | 65 dB |
| Speaker Connection | 4-pin Phoenix Connectors |
| Charger Output | 5 VDC, USB |
| Power Supply | 19 VDC / 3.5 A CE, CSA and UL Listed |
| Dimensions | 8 1/2" W x 1 3/4" H x 7 1/2" D |
| Weight | 1.7 lb |

Features

- Amplifier: digital hybrid class D
- Two Power Amplifiers: 25 watts ea. channel, total 50 watts RMS for 4 x 8 Ω loudspeakers
- 3 Line Level Inputs, mixed w/ the two microphone inputs
- 2 Line Level Outputs
 - › Rear panel mixed output for assistive listening system and/or lesson capture with gain control (3.5mm)
- Hybrid Learning Compatible
 - › Front panel input & output connects to host computer to synchronize classroom audio w/ video conference application
- Digital Feedback Guard™
- Switchable computer anti-hum circuit with ON/OFF switch
- 3-band digital equalizer \pm 10dB
- Power sleep mode to conserve energy
- Light weight aluminum cover
- Teacher Priority function attenuates volume of all line inputs with button press
- Drop-in microphone charger connection 5 VDC USB
- Accommodates up to 3 ceiling sensors for increased microphone reception coverage and/or extra-large classrooms
- WC-400 Wall Mounted Cabinet (optional)
- Rack or shelf/wall mounting kits (optional)